



# SOFTAIL®

# SPORT GLIDE® Model Specifications<sup>1</sup> FLSB

DIMENSIONS	
Length	<b>91.5 in.</b> (2325 mm)
Overall Width	<b>37.8 in.</b> (960 mm)
Overall Height	<b>44.1 in.</b> (1120 mm)
Seat Height:	
• Laden <sup>2</sup>	<b>25.7 in.</b> (653 mm)
• Unladen	<b>26.8 in.</b> (680 mm)
Ground Clearance	<b>4.7 in.</b> (120 mm)
Rake (steering head)	30°
Fork Angle	30°
Trail	<b>5.9 in.</b> (150 mm)
Wheelbase	<b>64 in.</b> (1625 mm)
Tires (Michelin® Scorcher® "31" front and rear):	
• Front	130/70B18 63H BW
• Rear	180/70B16 77H BW
Fuel Capacity	<b>5 gal.</b> (18.9 l)
(warning light at approximately 1 gal.)	
Oil Capacity (w/filter)	<b>5 qt.</b> (4.7 l)
Transmission Capacity	<b>1 qt.</b> (.95 l)
Primary Chain Case Capacity	<b>1.25 qt.</b> (1.18 l)
Weight:	
• As Shipped	<b>670 lb.</b> (304 kg)
• In Running Order	<b>699 lb.</b> (317 kg)
• Gross Vehicle Weight Rating	<b>1160 lb.</b> (526 kg)
• Gross Axle Weight Rating	
• Front	<b>450 lb.</b> (204 kg)
• Rear	<b>730 lb.</b> (331 kg)
Luggage Capacity:	
• Volume	<b>1.9 cu. ft.</b> (0.05 m <sup>3</sup> )
ENGINE	
Engine	Milwaukee-Eight® 107
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder
Bore x Stroke	<b>3.937 in. x 4.375 in.</b> (100 mm x 111 mm)
Displacement	<b>107 cu. in.</b> (1746 cc)
Compression Ratio	10.0:1
Fuel System <sup>3</sup>	Electronic Sequential Port Fuel Injection (ESPFI)
Air Cleaner	8.5 in. round, radial bolt cover with washable fiberglass filter media
Exhaust	2-into-1; catalyst in muffler
Lubrication System	Pressurized, dry-sump with oil cooler

DRIVETRAIN	
Primary Drive	Chain, 34/46 ratio
Final Drive	Belt, 32/66 ratio
Clutch	Mechanical, 10 plate wet, assist & conventional
Transmission	6-Speed Cruise Drive®
Gear Ratios (overall):	<b>U.S.</b>
• 1st	<b>9.311</b>
• 2nd	<b>6.454</b>
• 3rd	<b>4.793</b>
• 4th	<b>3.882</b>
• 5th	<b>3.307</b>
• 6th	<b>2.79</b>
CHASSIS	
Frame	Mild steel, tubular frame; rectangular section backbone; stamped, cast, and forged junctions; MIG welded; aluminum forged fender supports
Swingarm	Mild steel, tubular sections, stamped x-member, forged axle junctions; MIG welded; removable belt spacer
Front Forks	Single cartridge 43 mm inverted with aluminum fork triple clamps; triple rate spring
Rear Shocks	Hidden, free piston, coil-over monoshock; 43 mm stroke; toolless hydraulic pre-load adjustment
Wheels <sup>4</sup> :	Black, Machine Highlighted, Mantis Cast Aluminum
• Front	<b>18 in. x 3.5 in.</b> (457 mm x 89 mm)
• Rear	<b>16 in. x 5 in.</b> (432 mm x 127 mm)
Brakes:	
• Caliper Type	4-piston fixed front and 2-piston floating rear
• Rotor Type (diameter x width):	Front black, split 7-spoke floating rotor, rear solid, uniform expansion rotor
• Front	<b>11.8 in. x .2 in.</b> (300 mm x 5.1 mm)
• Rear	<b>11.5 in. x .23 in.</b> (292 mm x 5.8 mm)
• Anti-Lock Braking System	Standard
Suspension Travel:	
• Front Wheel	<b>5.1 in.</b> (130 mm)
• Rear Wheel	<b>3.4 in.</b> (86 mm)
PERFORMANCE	
Engine Torque <sup>5</sup> (per J1349):	
• North America	<b>108 ft. lb. @ 2750 rpm</b> (146 Nm @ 2750 rpm)
Lean Angle (per J1168):	
• Right	27.9°
• Left	28.7°
Fuel Economy <sup>6</sup> (Estimated City/Hwy)	<b>47 mpg</b> (5 l/100 km)

ELECTRIC	
Battery (per Battery Council International Rating)	Sealed, maintenance-free, absorbed glass mat (AGM) battery, 12V, 17.5Ah, 310 cca at 0°F
Charging	Three-phase, 42 amp system (390W @ 13V, 1000 rpm, 546W max power @ 13V, 2000 rpm)
Starting	1.6 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
• Headlamp	All LED, low beam, high beam and signature position lamp
• Tail/Stop Lights	Integrated LED
• Front Signal Lights	Incandescent bullets
• Indicator Lamps	High beam, turn signals, neutral, low oil pressure, engine diagnostics, cruise, ABS, security system <sup>7</sup> , low battery voltage, low fuel
• Rear Turn Signals	Integrated LED
Gauges	5-inch analog speedometer with digital gear, odometer, fuel level, clock, trip, range and tachometer indication
Electric Power Outlet	USB A-type; output 5V at 2.4A
WARRANTY	
Warranty <sup>8</sup>	<b>24 months</b> (unlimited mileage)
Service Interval <sup>9</sup>	First <b>1000 miles</b> (1600 km), every <b>5000 miles</b> (8000 km) thereafter

<sup>1</sup> Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

<sup>2</sup> Measurement reflects 180 lb. (81.7 kg) operator weight.

<sup>3</sup> Recommended 91 octane or higher fuel (R+M)/2.

<sup>4</sup> Standard and optional wheels may vary by country and region.

<sup>5</sup> Values shown are nominal. Performance may vary by country and region.

<sup>6</sup> The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

<sup>7</sup> North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

<sup>8</sup> See motorcycle Owner's Manual for complete details.

<sup>9</sup> Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.