



2021 FLHT ELECTRA GLIDE[®] STANDARD

DIMENSIONS

Notes

Length	94.5 in. (2,400 mm)	
Overall Width	38 in. (965 mm)	
Overall Height	55.3 in. (1,405 mm)	
Seat Height, Laden	26.1 in. (663 mm)	2
Seat Height, Unladen	26.8 in. (680 mm)	
Ground Clearance	4.7 in. (120 mm)	
Rake (steering head) (deg)	26	
Fork Angle (deg)	29.25	
Trail	6.7 in. (170 mm)	
Wheelbase	64 in. (1,625 mm)	
Tires, Type	Dunlop® Harley-Davidson Series, bias blackwall front and rear	
Tires, Front Model	D408F	
Tires, Front Specification	BW 130/80B17 65H	
Tires, Rear Model	D407T	
Tires, Rear Specification	BW 180/65B16 81H	
Fuel Capacity	6 gal. (22.7 l)	
Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)	
Oil Capacity (w/filter)	5 qt. (4.9 l)	
Transmission Capacity	1 qt. (.95 l)	
Primary Chain Case Capacity	1.1 qts. (1 l)	
Coolant Capacity	N/A	
Weight, As Shipped	781 lb. (354 kg)	
Weight, In Running Order	820 lb. (372 kg)	
Gross Vehicle Weight Rating	1,360 lb. (617 kg)	
Gross Axle Weight Rating, Front	500 lb. (227 kg)	
Gross Axle Weight Rating, Rear	927 lb. (420 kg)	
Luggage Capacity -Volume	2.3 cu ft (0.064 m ³)	

ENGINE

Engine	Milwaukee-Eight® 107
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder
Bore	3.937 in. (100 mm)
Stroke	4.375 in. (111 mm)

Displacement	107 cu in (1,746 cc)	
Compression Ratio	10.0:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	Paper, washable	
Exhaust	Chrome, 2-1-2 dual exhaust with tapered mufflers	
Lubrication System	Pressurized, dry-sump with oil cooler	

DRIVETRAIN

Primary Drive	Chain, 34/46 ratio	
Final Drive	Belt, 32/68 ratio	
Clutch	Mechanically actuated 10 plate wet, Assist and Slip	
Transmission	6-Speed Cruise Drive®	
Gear Ratios (overall) 1st	9.593	
Gear Ratios (overall) 2nd	6.65	
Gear Ratios (overall) 3rd	4.938	
Gear Ratios (overall) 4th	4	
Gear Ratios (overall) 5th	3.407	
Gear Ratios (overall) 6th	2.875	

CHASSIS

Frame	Mild steel; tubular frame; two-piece stamped and welded backbone; cast and forged junctions; twin downtubes; bolt-on rear frame with forged fender supports; MIG welded.	
Swingarm	Mild steel; two-piece drawn and welded section; forged junctions; MIG welded.	
Front Fork	49 mm Dual Bending Valve	
Rear Shocks	Premium Low Hand-Adjustable Rear Suspension	
Wheels, Front Type	Impeller Cast Aluminum	4
Wheels, Front Width	3 in. (76 mm)	
Wheels, Front Height	17 in. (432 mm)	
Wheels, Rear Type	Impeller Cast Aluminum	4
Wheels, Rear Width	5 in. (127 mm)	
Wheels, Rear Height	16 in. (406 mm)	
Brakes, Caliper Type	32 mm, 4-piston fixed front and rear	
Brakes, Rotor Type	Dual floating rotors (front), fixed rotor (rear)	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.2 in. (5.1 mm)	
Brakes, Front is dual	Yes	
Brakes, Rear Diameter	11.8 in. (300 mm)	
Brakes, Rear Thickness	0.28 in. (7.1 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.6 in. (117 mm)	
Suspension Travel, Rear	2.15 in. (55 mm)	

PERFORMANCE

Engine Torque Testing Method	J1349
------------------------------	-------

Engine Torque	111 ft-lb (151 Nm)	5
Engine Torque (rpm)	3,250	
Lean Angle Testing Method	J1168	
Lean Angle, Right (deg.)	31	
Lean Angle, Left (deg.)	29	
Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	43 mpg (5.5 l/100 km)	6

ELECTRIC

Battery	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca (per Battery Council International Rating)	
Charging	Three-phase, 48-amp system (600W @ 13V, 2000 rpm, 625W max power @ 13V)	
Starting	1.6 kW electric with solenoid shift starter motor engagement	
Lights (as per country regulation), Headlamp	Dual halogen headlight 55-watt 625 lumen low beam, 65-watt 1,570 high beam	
Lights (as per country regulation), Tail/Stop	8W/28W	
Lights (as per country regulation), Front Signal Lights	8W/28W	
Lights (as per country regulation), Indicator Lamps	High beam, running lights, directional lights, low oil pressure, engine diagnostics, neutral, cruise control, accessory, battery, gear indication, security system, 6-speed, low fuel warning, ABS, miles to empty display, fog/aux lamp indicator	7
Lights, Rear Turn Signals	27W	
Gauges	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	
Auxiliary Lamps	N/A	
Electric Power Outlet	Electric power accessory port in fairing	
GPS System	N/A	
Reverse Gear	N/A	

WARRANTY AND SERVICE

Warranty	24 months (unlimited mileage)	8
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter	9

FOOTNOTES

1

Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

2

Measurement reflects 180 lb. (81.7 kg) operator weight.

3

Recommended 91 octane or higher fuel (R+M)/2.

4

Standard and optional wheels may vary by country and region.

5

Values shown are nominal. Performance may vary by country and region.

6

The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

7

North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

8

See motorcycle owner's manual for complete details.

9

Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.