

MODEL YEAR 2023 | ROAD GLIDE LIMITED

Dimensions	FLTRK Road Glide® Limited	Notes
Length	102.2 in. (2,595 mm)	
Overall Width	36.6 in. (930 mm)	
Overall Height	56.1 in. (1,425 mm)	
Seat Height, Laden	27.2 in. (690 mm)	2
Seat Height, Unladen	28.9 in. (735 mm)	
Static Ground Clearance	5.1 in. (130 mm)	
Rake (steering head) (deg)	26	
Fork Angle (deg)	29.25	
Trail	6.7 in. (170 mm)	
Wheelbase	64 in. (1,625 mm)	
Tires, Type	Dunlop® Harley-Davidson Series, bias blackwall front and rear	
Tires, Front Model	D408F	
Tires, Front Specification	BW 130/70B18 63H	
Tires, Rear Model	D407T	
Tires, Rear Specification	BW 180/55B18 80H	
Fuel Capacity	6 gal. (22.7 l)	
Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)	
Oil Capacity (w/filter)	5 qt. (4.7 l)	
Transmission Capacity	1 qt. (.95 l)	
Primary Chain Case Capacity	1.1 qts. (1 l)	
Coolant Capacity	0.8 qt. (0.76 l)	
Weight, As Shipped	897 lb. (407 kg)	
Weight, In Running Order	932 lb. (423 kg)	
Gross Vehicle Weight Rating	1,360 lb. (617 kg)	
Gross Axle Weight Rating, Front	500 lb. (227 kg)	
Gross Axle Weight Rating, Rear	927 lb. (420 kg)	
Luggage Capacity -Volume	4.7 cu ft (0.132 m3)	

Engine	FLTRK Road Glide® Limited	Notes
Engine	Twin-Cooled™ Milwaukee-Eight® 114	
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder	
Bore	4.016 in. (102 mm)	
Stroke	4.5 in. (114.3 mm)	
Displacement	114 cu in (1,868 cc)	
Compression Ratio	10.5:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	Paper, washable	
Exhaust	2:1:2 dual exhaust with 4 in. tapered mufflers	
Lubrication System	Pressurized, dry-sump with oil cooler	
Drivetrain	FLTRK Road Glide® Limited	
Primary Drive	Chain, 34/46 ratio	
Final Drive	Belt, 32/68 ratio	
Clutch	Mechanically actuated 10 plate wet, Assist and Slip	
Transmission	6-Speed Cruise Drive®	
Gear Ratios	9.593	
Gear Ratios	6.65	
Gear Ratios	4.938	
Gear Ratios	4	
Gear Ratios	3.407	
Gear Ratios	2.875	

Chassis	FLTRK Road Glide® Limited	Notes
Frame	Mild steel; tubular frame, two-piece stamped and welded backbone; cast and forged junctions; twin down tubes; bolt-on rear frame with forged fender supports; MIG welded	
Swingarm	Mild steel, two piece drawn and welded section; forged junctions; MIG welded	
Front Fork	49mm Dual Bending Valve	
Rear Shocks	Premium standard height hand-adjustable rear suspension	

Wheels, Optional Style Type	Gloss Black Slicer II	4
Wheels, Front Type	Slicer II cast aluminum with clear coat	4
Wheels, Front Width	3.5 in. (89 mm)	
Wheels, Front Height	18 in. (457 mm)	
Wheels, Rear Type	Slicer II cast aluminum with clear coat	4
Wheels, Rear Width	5 in. (127 mm)	
Wheels, Rear Height	18 in. (457 mm)	
Brakes, Caliper Type	32 mm, 4-piston fixed front and rear	
Brakes, Rotor Type	Dual floating rotors (front), fixed rotor (rear)	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.2 in. (5.1 mm)	
Brakes, Front is dual	Yes	
Brakes, Rear Diameter	11.8 in. (300 mm)	
Brakes, Rear Thickness	0.28 in. (7.1 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.6 in. (117 mm)	
Suspension Travel, Rear	3 in. (76 mm)	

Performance	FLTRK Road Glide® Limited	Notes
Engine Torque Testing Method	J1349	
Engine Torque	122 ft-lb (166 Nm)	5
Engine Torque	2,750	
Power	93 HP / 69 kW @ 5020 rpm	
Lean Angle Testing Method	J1168	
Lean Angle, Right (deg.)	32	
Lean Angle, Left (deg.)	32	
Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	43 mpg (5.5 l/100 km)	6
CO ² Emissions Testing Method	N/A	
CO ² Emissions	N/A	

Electric	FLTRK Road Glide® Limited	Notes
Battery	Sealed, maintenance-free, 12V, 28-amp/hour,	

	405 cca (per Battery Council International Rating)	
Charging	Three-phase, 48-amp system (600W @ 13V, 2000 rpm, 625W max power @13V)	
Starting	1.6 kW electric with solenoid shift starter motor engagement	
Lights (as per country regulation), Headlamp	LED 40-watt, 1,060 lumen low beam, 60-watt, 1,560 lumen high beam	
Lights (as per country regulation), Tail/Stop	8W/28W	
Lights (as per country regulation), Front Signal Lights	8W/28W	
Lights, Rear Turn Signals	LED	
Gauges	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	
Auxiliary Lamps	N/A	
Electric Power Outlet	Electric power accessory port in fairing and tourpak	
GPS System	Boom! Box GTS audio system with GPS and touchscreen	
Reverse Gear	N/A	

Warranty And Service	FLTRK Road Glide® Limited	Notes
Warranty	24 months (unlimited mileage)	7
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter	8

Footnotes	FLTRK Road Glide® Limited	
1	Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without	

	<p>incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.</p>
2	Measurement reflects 180 lb. (81.7 kg) operator weight.
3	Recommended 91 octane or higher fuel (R+M)/2.
4	Standard and optional wheels may vary by country and region.
5	Values shown are nominal. Performance may vary by country and region.
6	The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.
7	See motorcycle owner's manual for complete details.
8	Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

©2023 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.