

MODEL YEAR 2024 | ROAD KING[®] SPECIAL

Dimensions	FLHRXS Road King [®] Special	Notes
Length	95.3 in. (2,420 mm)	
Overall Width	39 in. (990 mm)	
Overall Height	45.3 in. (1,150 mm)	
Seat Height, Laden	26.4 in. (671 mm)	2
Seat Height, Unladen	27.4 in. (695 mm)	
Static Ground Clearance	4.9 in. (125 mm)	
Rake (steering head) (deg)	26	
Fork Angle (deg)	29.25	
Trail	6.9 in. (175 mm)	
Wheelbase	64 in. (1,625 mm)	
Tires, Type	Dunlop [®] Harley-Davidson Series, bias blackwall front and rear	
Tires, Front Model	D408F	
Tires, Front Specification	130/60B19 61H	
Tires, Rear Model	D407T	
Tires, Rear Specification	180/55B18 80H	
Fuel Capacity	6 gal. (22.7 l)	
Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)	
Oil Capacity (w/filter)	5.2 qt. (4.9 l)	
Transmission Capacity	1 qt. (.95 l)	
Primary Chain Case Capacity	1.1 qts. (1 l)	
Coolant Capacity	N/A	
Weight, As Shipped	774 lb. (351 kg)	
Weight, In Running Order	807 lb. (366 kg)	
Gross Vehicle Weight Rating	1,360 lb. (617 kg)	
Gross Axle Weight Rating, Front	500 lb. (227 kg)	
Gross Axle Weight Rating, Rear	927 lb. (420 kg)	
Luggage Capacity -Volume	2.5 cu ft (0.07 m3)	

Engine	FLHRXS Road King® Special	Notes
Engine	Milwaukee-Eight® 114	
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder	
Bore	4.016 in. (102 mm)	
Stroke	4.5 in. (114.3 mm)	
Displacement	114 cu in (1,868 cc)	
Compression Ratio	10.5:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	Paper, washable	
Exhaust	Black, 2-1-2 dual exhaust with tapered mufflers	
Lubrication System	Pressurized, dry-sump with oil cooler	

Drivetrain	FLHRXS Road King® Special	Notes
Primary Drive	Chain, 34/46 ratio	
Final Drive	Belt, 32/68 ratio	
Clutch	Mechanically actuated, 10 plate wet, Assist and Slip	
Transmission	6-Speed Cruise Drive®	
Gear Ratios	9.593	
Gear Ratios	6.65	
Gear Ratios	4.938	
Gear Ratios	4	
Gear Ratios	3.407	
Gear Ratios	2.875	

Chassis	FLHRXS Road King® Special	Notes
Frame	Mild steel; tubular frame; two-piece stamped and welded backbone; cast and forged junctions; twin down-tubes; bolt-on rear frame with forged fender supports; MIG welded.	

Swingarm	Mild steel; two-piece drawn and welded section; forged junctions; MIG welded.	
Front Fork	49 mm Dual Bending Valve	
Rear Shocks	Premium low height hand-adjustable rear suspension	
Wheels, Optional Style Type	N/A	4
Wheels, Front Type	Gloss Black Prodigy	4
Wheels, Front Diameter	19 in. (483 mm)	
Wheels, Front Width	3.5 in. (89 mm)	
Wheels, Rear Type	Gloss Black Prodigy	4
Wheels, Rear Diameter	18 in. (457 mm)	
Wheels, Rear Width	5 in. (127 mm)	
Brakes, Caliper Type	32 mm, 4-piston fixed front and rear	
Brakes, Rotor Type	Dual floating rotors (front), fixed rotor (rear)	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.2 in. (5.1 mm)	
Brakes, Front is dual	Yes	
Brakes, Rear Diameter	11.8 in. (300 mm)	
Brakes, Rear Thickness	0.28 in. (7.1 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.6 in. (117 mm)	
Suspension Travel, Rear	2.1 in. (54 mm)	

Performance	FLHRXS Road King® Special	Notes
Engine Torque Testing Method	J1349	
Engine Torque	122 ft-lb (165 Nm)	5
Engine Torque	2,750	
Power	95 HP / 71 kW @ 5020 rpm	
Lean Angle Testing Method	J1168	
Lean Angle, Right (deg.)	32	
Lean Angle, Left (deg.)	31	
Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	43 mpg (5.5 l/100 km)	6
CO ₂ Emissions Testing Method	N/A	
CO ₂ Emissions	N/A	

Electric	FLHRXS Road King® Special	Notes
Battery	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca (per Battery Council International Rating)	
Charging	Three-phase, 48-amp system (600W @ 13V, 2000 rpm, 625W max power @ 13V)	
Starting	1.6 kW electric with solenoid shift starter motor engagement	
Lights (as per country regulation), Headlamp	LED 34-watt, 915 lumen low beam, 37-watt, 915 lumen high beam	
Lights (as per country regulation), Tail/Stop	8W/28W	
Lights (as per country regulation), Front Signal Lights	8W/28W	
Lights, Rear Turn Signals	8W/28W	
Gauges	Gauges styled to complement each vehicle. Display features odometer, trip A, trip B, range to empty and gear indicator; and larger tell-tale indicators.	
Auxiliary Lamps	N/A	
Electric Power Outlet	N/A	
GPS System	N/A	
Reverse Gear	N/A	

Warranty And Service	FLHRXS Road King® Special	Notes
Warranty	24 months (unlimited mileage)	7
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter	8

Footnotes	FLHRXS Road King® Special	
1	Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur	

	and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.	
2	Measurement reflects 180 lb. (81.7 kg) operator weight.	
3	Recommended 91 octane or higher fuel (R+M)/2.	
4	Standard and optional wheels may vary by country and region.	
5	Values shown are nominal. Performance may vary by country and region.	
6	The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.	
7	See motorcycle owner's manual for complete details.	
8	Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.	

©2024 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.