

# MODEL YEAR 2025 | NIGHTSTER SPECIAL

Dimensions	RH975S Nightster® Special	Notes
Length	89.2 in. (2,265 mm)	
Overall Width	33.9 in. (860 mm)	
Overall Height	46.7 in. (1,185 mm)	
Seat Height, Laden	27.1 in. (688 mm)	2
Seat Height, Laden (Low seat position)		
Seat Height, Laden (High seat position)		
Seat Height, Laden (Low seat position with optional ARH suspension)		
Seat Height, Laden (High seat position with optional ARH suspension)		
Seat Height, Unladen	28.1 in. (715 mm)	
Seat Height, Unladen (Low seat position)		
Seat Height, Unladen (High seat position)		
Seat Height, Unladen (Low seat position with optional ARH suspension)		
Seat Height, Unladen (High seat position with optional ARH suspension)		
Static Ground Clearance	4.7 in. (120 mm)	
Dynamic Ground Clearance (with optional suspension)		
Rake (steering head)	30	
Fork Angle	28	
Trail	5.4 in. (137 mm)	
Wheelbase	60.8 in. (1,545 mm)	
Tires, Type	Dunlop® Harley-Davidson Series Bias Blackwall	
Tires, Front Model	D401F	
Tires, Front Specification	100/90-19 57H	
Tires, Rear Model	D401T	
Tires, Rear Specification	150/80B16 77H	
Fuel Capacity	3.1 gal. (11.7 l)	

Reserve Fuel Capacity, Fuel Injection (warning light)	0.8 gal. (3 l)	
Oil Capacity (w/filter)	4.75 qt. (4.5 l)	
Transmission Capacity	N/A	
Primary Chain Case Capacity	N/A	
Coolant Capacity	2.22 qt. (2.1 l)	
Weight, As Shipped	476 lb. (216 kg)	
Weight, In Running Order	496 lb. (225 kg)	
Gross Vehicle Weight Rating	922 lb. (418 kg)	
Gross Axle Weight Rating, Front	353 lb. (160 kg)	
Gross Axle Weight Rating, Rear	595 lb. (270 kg)	
Luggage Capacity -Volume	N/A	

Engine	RH975S Nightster® Special	Notes
Engine	Revolution® Max 975T	
Valves	Chain-driven, DOHC, hydraulic self-adjusting lifters, intake VVT; four valves per cylinder	
Bore	3.82 in. (97 mm)	
Stroke	2.6 in. (66 mm)	
Displacement	59.5 cu in (975 cc)	
Compression Ratio	12:01	
Fuel System	Electronic Sequential Port Fuel Injection (ESPFI)	3
Air Cleaner	Downdraft intake, tuned velocity stacks, washable filter media	
Exhaust	2-into-1; catalyst in header	
Lubrication System	Semi-Dry Sump	

Drivetrain	RH975S Nightster® Special	Notes
Primary Drive	Gear, 49/89 ratio	
Final Drive	Belt, 34/80 ratio	
Clutch	Mechanical, 8 plate wet, assist & slip, 1090N	
Transmission	6-speed	
Gear Ratios (overall) 1st	12.21	
Gear Ratios (overall) 2nd	9.022	

Gear Ratios (overall) 3rd	6.994	
Gear Ratios (overall) 4th	5.641	
Gear Ratios (overall) 5th	4.731	
Gear Ratios (overall) 6th	4.131	

<b>Chassis</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Frame	Stressed-member, high strength low alloy steel trellis frame; stamped, cast, and forged junctions; MIG welded; aluminum forged mid-structure	
Swingarm	Mild steel, rectangular tube section, stamped x-member; MIG welded	
Front Fork	41 mm SHOWA® Dual Bending Valve conventional forks. Aluminum fork triple clamps.	
Front Fork, Optional		
Rear Shocks	Rear suspension is dual outboard, direct-acting (no linkage) emulsion technology shock absorbers with coil springs and a threaded collar for pre-load adjustment.	
Rear Shocks, Optional		
Wheels, Optional Style Type	N/A	4
Wheels, Front Type	Aluminum cast, silver	4
Wheels, Front Diameter	19 in. (483 mm)	
Wheels, Front Width	2.5 in. (64 mm)	
Wheels, Rear Type	Aluminum cast, silver	4
Wheels, Rear Diameter	16 in. (406 mm)	
Wheels, Rear Width	4.25 in. (108 mm)	
Brakes, Caliper Type	Front: axially mounted, 4-piston caliper; Rear: floating, single piston caliper	
Brakes, Rotor Type	Front: single rotor, floating, hub - mounted; Rear: solid uniform expansion rotor	
Brakes, Front Diameter	12.6 in. (320 mm)	
Brakes, Front Thickness	0.23 in. (5.8 mm)	
Brakes, Front is dual	No	
Brakes, Rear Diameter	10.2 in. (260 mm)	
Brakes, Rear Thickness	0.2 in. (5 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.5 in. (114 mm)	

Suspension Travel, Rear	3 in. (76.2 mm)	
-------------------------	-----------------	--

<b>Performance</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Engine Torque Testing Method	J1349	
Engine Torque	72 ft-lb (97 Nm)	5
Engine Torque (rpm)	5,750	
Power	91 HP / 68 kW @ 7500 rpm	
Lean Angle Testing Method	J1168	
Lean Angle, Right (deg.)	32	
Lean Angle, Left (deg.)	32	

<b>Electric</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Battery	Sealed, maintenance-free, absorbed glass mat (AGM) battery, 12V, 12Ah, 225 CCA at 0°F	
Charging	Three-phase, 45 Amp system (300 Watts @13 Volts, 1200 rpm, 585 Watts max power @ 13 Volts, 2250 rpm)	
Starting	0.9 kW electric with direct drive starter motor engagement	
Lights (as per country regulation), Headlamp	All LED headlamp, low and high beam with signature position lighting	
Lights (as per country regulation), Tail/Stop	All LED rear lighting	
Lights (as per country regulation), Front Signal Lights	LED Bullet Turn Signals	
Lights, Rear Turn Signals	LED Bullet Turn Signals	
Gauges	4 inch viewable area TFT display with speedometer, gear, odometer, fuel level, clock, trip, ambient temp, low temp alert, side stand down alert, TIP over alert, cruise, range and tachometer indication BT capable - phone pairing to access phone calls, music, navigation (H-D App ONLY)	
Auxiliary Lamps	N/A	
Electric Power Outlet	USB C-Type , Output 5V at 2.4 Amp	
GPS System	N/A	
Reverse Gear	N/A	
Fuel Economy & CO <sub>2</sub> Emissions	RH975S Nightster® Special	

Fuel Economy Testing Method	Estimated City/Hwy	
Fuel Economy	52 mpg (4.5 l/100 km)	

<b>Infotainment</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Infotainment system	N/A	
Screen Size	4 in (102 mm)	
Type	Color TFT	
Watts Per Channel	N/A	
Speakers	N/A	
Speaker Size	N/A	
Headset Specifications (if equipped)	Bluetooth	
AM	N/A	
FM	N/A	
MW	N/A	
LW	N/A	
Weather Band (WB)	N/A	
SD Card, Flash Drive and MP3 - via USB Connection	N/A	
Hands-free Mobile Phone - via Bluetooth	Standard	
Voice Recognition Languages: Phone functions only	Phone dependent	
Rider/Passenger Intercom	Headset function only	
Vehicle Information Screen (Air temperature, oil pressure and EITMS)	TPMS, Engine temp, Battery Voltage, Ambient Air Temp	
Text-to-Speech (TTS) Languages	Phone dependent	
USB	Charging and Instrument update, USB-C, 5V, 3A	
Phone Connectivity		
Bluetooth	Phone/Media Supported	
Navigation - via Bluetooth		

<b>Rider Safety Enhancements</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Anti-lock Brake System (ABS)	Included	
Electronic Linked Braking (ELB)	N/A	
Traction Control System (TCS)	Included	

Drag-torque Slip Control System (DSCS)	Included	
Vehicle Hold Control (VHC)	N/A	
Tire Pressure Monitoring System (TPMS)	Included	
Wheel Lift Mitigation	N/A	

<b>Cornering Rider Safety Enhancements</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Cornering Enhanced Anti-lock Brake System (C-ABS)	N/A	
Cornering Enhanced Electronic Linked Braking (C-ELB)	N/A	
Cornering Enhanced Traction Control System (C-TCS)	N/A	
Cornering Drag-Torque Slip Control System (C-DSCS)	N/A	
Enhanced Lift Mitigation	N/A	

<b>Warranty And Service</b>	<b>RH975S Nightster® Special</b>	<b>Notes</b>
Warranty	24 months (unlimited mileage)	6
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter	7

<b>Footnotes</b>	<b>RH975S Nightster® Special</b>	
1	Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories	

	described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.	
2	Measurement reflects 180 lb. (81.7 kg) operator weight.	
3	Recommended 91 octane or higher fuel (R+M)/2.	
4	Standard and optional wheels may vary by country and region.	
5	Values shown are nominal. Performance may vary by country and region.	
6	See motorcycle owner's manual for complete details.	
7	Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.	

©2025 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.